

TECH SHEET

MAIN FEATURES


Suitable environment	indoor/outdoor
Handheld	yes
Wearable	yes (optional tool)
Mountable on various mobile platforms (car, trolley, bike, quad, boat, robot)	yes
SLAM post-processing software included (HERON Desktop)	yes
Point cloud advanced processing software included (Reconstructor)	yes
Free software for x-ray maps visualization and measuring included (GoBlueprint)	yes
Output data	.e57, .las, .ply, export to ReCap
Points per second	640,000
Local accuracy	±4 mm
Max survey resolution	1 cm
Global accuracy	±2 cm in short close rings ⁽¹⁾
Control points acquisition	yes
Global accuracy with control points	±1 cm
Loop closure	not mandatory
Usable in every light conditions	yes
Initialization and calibration procedures	not required
Single operator	yes
Sensors working time (in continuous acquisition)	~ 1h 30min (more with extra batteries)
Operating temperature	-10° ; +45°
Storage temperature	-40° ; +60°
Rugged transport case	yes

SYSTEM CONTROLLER

Weight Dimensions	1085 g 160 x 209 x 59 mm
Processor	Intel® 11 th Gen Core™ (4.1 GHz)
• PENDRIVE for data storage	USB 3.1 Gen 1
Memory size	256 GB
Max read speed	up to 300 MB/sec
Max write speed	up to 100 MB/sec
• INTERNAL BATTERY	Li-ion battery
Capacity	6700 mAh 80.4 Wh
Output	12 V
Working time	~ 1h 30min (more with extra "plug&go" batteries)

HANDHELD POLE

Weight (with cable)	965 g
Length	from 400 to 1300 mm



CAPTURE HEAD (DETACHABLE)

Weight Dimensions	1650 g 261 x 140 X 120 mm
---------------------	-----------------------------

COMPONENTS:

• LASER SENSOR	32 chs Class 1 Eye Safe
Wavelength	905 nm
FOV	360° x 360° ⁽²⁾
Range	0.5 - 300 m
• IMU	yes
• RGB PANO CAMERA (MG1)	n. 1 4 lenses
Continuous acquisition	24 Hz 4K Ultra HD
Single shot acquisition	8K
FOV	360°
Auto color/light balance	yes
Auto exposure control	yes ⁽³⁾

PDA CONTROL UNIT

Personal Digital Assistant

Weight Dimensions	560 g 167 x 81.4 x 15.5 mm
Processor	Helio G95 Octa Core 2.1 GHz
Display	6.22" LCD HD + waterdrop screen
Battery	Li-ion 6350 mAh
Battery charging	24 W Type-C fast charge
Battery working time	15 ÷ 24 h (depending on the display intensity)

TECH SHEET

OPTIONAL TOOLKITS

Extra batteries	standard "plug&go" ~ 1h 30min 445 g
Telescopic poles	from 560 to 1800 mm 1000 g
	from 1000 to 6000 mm 1880 g
Tilt adapter for Capture Head	Ø32 x 175 mm 200 g

Centering tip	150 mm 12 g
Rugged backpack	540 x 400 x 220 mm 4850 g cabled
Car mount	case: 547 x 427 x 251 mm 9000 g
Ring LED Light	Ø126 x 184 mm 700 g 4000 lm 36 W

SOFTWARE EQUIPMENT

Reconstructor	included
Reconstructor HERON add-on	included
3D navigation of point clouds and images	yes
Automatic scans registration	yes
Import	TLS data, .ifc BIM, point clouds from UAV, mobile mapping data
Direct import formats	.laz, .e57, .fls, .zfs, .rxp, .x3s, .x3m, .clr, .cl3, .dp, .ixf, .nctri, .txt, .las, .ptx, .pts, .ptg, .asc, .ply, .csv, DEM Ascii
Point cloud filtering, managing and classifying	yes
CAD/Mesh models	.3ds, .ifc, .obj, .dxf, .stl, .txt, .wrl, .vrml, .ply, .mvx, .dae
Mesh creation and manipulation	yes
Volumes and areas computation	yes
Cross sections and profiles (.dxf)	yes
Verification tool	yes
Orthophotos/x-Ray orthophotos (direct export to AutoCAD)	yes
Direct export of 3D point clouds and 2D maps	.las, .e57 with images, ReCap, AutoCAD
Cloud sharing	AtisCloud, Benaco, Cintoo Cloud, FARO Webshare, Geo-Plus, Topcon CollageWeb

HERON Desktop	included
Drift effect reducing (global optimization)	yes
3D local maps patented algorithm	yes
Large coordinates for geolocalization	yes
Split/merge trajectories and point clouds	yes
Automatic post-processing mode	yes
Noise cleaning (attenuation)	yes
Moving objects removing	yes
Constraints tool (control points/control scans)	yes

GoBlueprint	free software
Measures on x-Ray maps directly (lines, angles, areas)	yes
Volume calculation based on x-Ray maps	yes
For any Windows-based PC and tablet (to easily bring your maps on-site too)	yes
Deliverables easy to manage and share	yes

Reconstructor 3D Viewer	free software
3D model navigation and immersive tour at 8K	yes

HERON Tracking add-on	optional
Reconstructor MINING add-on	optional
Reconstructor COLOR add-on	optional
ClearEdge3D EdgeWise Verity Rithm	optional
Cintoo Cloud	optional

(1) The global accuracy depends on the effectiveness of the SLAM registration algorithm, which can be influenced by the geometry of the surveyed environment. Long trajectories in absence of loop closures and cross paths, such as narrow tunnels or narrow stairs, can downgrade the global accuracy to 2-3 cm. The patented and unique algorithms present in HERON Desktop and the use of control points or control scans as constraints can dramatically improve the quality of the global accuracy up to 1 cm. The Gexcel support team is always ready to provide you with more detailed information on this topic.

(2) Final FOV guaranteed by walking with the system.

(3) The camera may not perform optimally in dark places. In these cases, we suggest the use of the *Ring LED Light* optional kit.

HERON, Reconstructor, and GoBlueprint are Gexcel trademarks. All rights reserved. Third-party software included in these pages are trademarks. All rights reserved to the companies that own the software. Gexcel is not affiliated with any of third-party software listed on these pages.

HERON is developed under a licence of the European Commission Joint Research Centre.